Datasheet

LuxaLight LED Engine Near Infrared 860nm Protected (24 Volt, 108 LEDs, 2835, IP64)

LE-24-860-108X2835PLX

Version: 2025-02-26.1

Email: info@luxalight.eu

Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04

Product description

The LuxaLight Industrial LED Engine, designed for high-performance applications, is optimized for processes requiring light in the near-infrared spectrum. With a wavelength of 860nm, this LED engine provides an efficient solution for applications such as medical treatments, material testing, and scientific research that benefit from infrared light.

This LED engine is a semi-finished product, which allows easy integration into custom systems or housings depending on your specific needs. It is ideal for use in various industrial, research, and medical applications, where the 860nm wavelength can provide the desired results. The engine is designed for seamless integration into larger systems or custom enclosures.

Key Features:

- 860nm Wavelength: The 860nm wavelength is ideal for applications requiring near-infrared light, such as material testing, medical therapies, and specific scientific processes.
- 24V Power Supply: The LED engine operates on a reliable 24V power supply, ensuring stable and consistent operation, perfect
 for demanding industrial and research applications.
- **High Radiation Intensity:** This LED engine delivers high radiation intensity, making it suitable for high-efficiency processes that require significant light output in the infrared spectrum.
- Semi-Finished Product: The LED engine can be integrated into custom systems or housings, offering flexibility for various industrial, research, or medical setups.
- Integration with MaNima Pollux Industry Pulsing (Strobing): The LED engine is compatible with the MaNima Pollux Industry System for pulsing (strobing), enhancing radiation intensity for faster reactions and improved efficiency in industrial processes.
- Real-Time Temperature Monitoring via NTC Sensor: The integrated NTC sensor ensures continuous temperature measurement
 and adjustment through the MaNima Pollux Industry System, maintaining optimal operating conditions for maximum radiation
 output.

Applications:

- Medical Therapy: The 860nm wavelength is effective for various therapeutic applications, including tissue healing, pain relief, and promoting circulation, often used in photobiomodulation (PBM) treatments.
- Material Testing & Quality Control: This LED engine is ideal for testing materials that react to infrared light, useful in industrial settings for evaluating the quality and integrity of different materials.
- Biological & Scientific Research: The 860nm wavelength is beneficial for various research fields, such as studying biological processes, enhancing cell growth, and promoting deep tissue regeneration.
- Medical Equipment: The engine can be integrated into medical devices designed for infrared treatments, such as those used for
 physiotherapy, pain management, and deep tissue therapy.
- Industrial Applications: The LED engine can be used in processes requiring infrared light for material curing, heat testing, and other industrial applications.

Benefits:

- High Radiation Intensity: The engine provides high radiation intensity, allowing for faster reactions and increased productivity in infrared applications.
- Flexible Integration: As a semi-finished product, it can be easily integrated into custom housings or systems tailored to specific applications.
- Efficient Performance: The engine delivers consistent, efficient performance, ideal for demanding environments that require stable light output.
- Real-Time Temperature Monitoring: The integrated NTC sensor, in combination with the MaNima Pollux Industry System, ensures consistent temperature management for optimal performance and reliability over time.

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04

KvK-nummer: 57580561

BTW-nummer: NL852642209B01

IBAN: NL87 INGB 0007 8159 75

BIC/SWIFT code: INGBNL2A

Technical specifications

General						
Brand	LuxaLight	LuxaLight				
Application	Hyper - spectral Imaging Machine Vision					
LED type	2835					
PCB color	White	White				
Material	Aluminum	Aluminum				
Dimensions	200 × 20 × 2 mm	200 × 20 × 2 mm				
Mounting	3M tape VHB4905	3M tape VHB4905				
Warranty	5 years	5 years				
Warranty	70000	70000				
LEDs per piece	108.00					
Lighting						
Wave length	860 nm	860 nm				
Beam angle	120 °	120 °				
Measurement results						
Irradiance	Value	Measuring distance				
	522 W/m2	25 mm				
	283 W/m2	50 mm				
	161 W/m2	75 mm				
	110 W/m2	100 mm				
	37,1 W/m2	200 mm				
	19,6 W/m2	300 mm				
Electronics						
Working voltage	24V					
Current per piece	1.25 A / piece					
Power consumption per piece	30.00 W / piece	30.00 W / piece				
PCB material	Aluminium	Aluminium				
Environmental						
Operating temperature	-20 ~ +60 °C	-20 ~ +60 °C				
Storage temperature	-40 ~ +80 °C	-40 ~ +80 °C				
IP class	IP 64	IP 64				
Directives - standards - certificates						
Directives	RoHS CE					
Safety standards	EN60598-1 EN62031 IEC62471					

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04

Measurement results

Email: info@luxalight.eu Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.

KvK-nummer: 57580561 BTW-nummer: NL852642209B01 IBAN: NL87 INGB 0007 8159 75 BIC/SWIFT code: INGBNL2A Email: info@luxalight.eu Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04