

## Datasheet

### **LuxaLight Industrial LED Fixture quartzglass UV-A 365nm 3535 60° 26.6x23.5mm (24 Volt, 3535, IP64, 60 LEDs)**

**LF-24-365-24.2X16-60-QG**

**Version: 2025-02-25.2**

## Product description

The **LuxaLight Industrial UV LED Fixture** is designed for intensive industrial applications requiring high radiation intensity for a wide range of processes, including material curing, reactors, disinfection, and more. With a wavelength of 365nm, this LED fixture provides a reliable and efficient solution for curing coatings, resins, and other materials, as well as accelerating chemical reactions in photochemical processes, supporting reactors, and disinfecting surfaces.

The LED fixture is equipped with a silicone coating on the PCB, offering extra protection against moisture, dust, and other environmental factors. The transparent cover is made of quartz glass, ensuring optimal transmission of the 365nm wavelength, allowing the radiation to reach the treated surface effectively.

### Key Features:

- **365nm Wavelength:** The 365nm wavelength is ideal for a wide range of industrial applications, including curing resins, coatings, and materials, as well as photochemical processes, reactors, and disinfection.
- **LED's with 60-Degree Optics:** The LED's are equipped with 60-degree optics, which ensures that the radiation is directed precisely to the right spot. This increases efficiency by focusing the UV-A light on the treatment surface, resulting in better performance in applications where accuracy and targeted radiation are crucial.
- **24V Power Supply:** The fixture operates on a reliable 24V power supply, ensuring stable and consistent operation, perfect for demanding industrial applications.
- **Silicone Coating on PCB:** The PCB is coated with silicone to protect against environmental factors like moisture and dust, ensuring durability in harsh industrial environments.
- **Transparent Quartz Glass Cover:** The transparent cover is made of quartz glass, which optimally transmits the 365nm wavelength, ensuring efficient radiation transfer to the treated surface.
- **Integration with MaNima Pollux Industry Pulsing (Strobing):** The LED fixture supports integration with the MaNima Pollux Industry System for pulsing (strobing), significantly increasing radiation intensity. This feature allows for faster reactions and improved efficiency in industrial processes.
- **Real-Time Temperature Monitoring via NTC Sensor:** The integrated NTC sensor ensures continuous temperature measurement and adjustment through the MaNima Pollux Industry System. This maintains the optimal operating temperature for maximum radiation output and consistent performance.

### Applications:

- **UV Curing of Coatings:** Ideal for curing coatings in the printing industry, such as in the paint industry, where rapid curing is essential for productivity.
- **Reactors and Chemical Processes:** Perfect for accelerating photochemical reactions, such as in reactors for resin or other material production that rely on UV light.
- **Disinfection:** The 365nm wavelength can be used for disinfecting surfaces, particularly in controlled industrial environments such as laboratories and cleanrooms.
- **3D Printing:** Suitable for accelerating the curing of 3D printed objects, especially for resins that require a specific 365nm wavelength for full curing.
- **Packaging Industry:** The LED fixture is ideal for curing packaging materials, such as in the food or pharmaceutical industry, ensuring rapid curing of printed materials.


### Benefits:

- **High Radiation Intensity:** The ability to pulse with the MaNima Pollux Industry System allows radiation intensity to be significantly increased, resulting in faster reactions and increased productivity.
- **Real-Time Temperature Monitoring for Consistent Performance:** The NTC sensor, combined with the MaNima Pollux Industry System, ensures continuous temperature measurement, helping to maintain the optimal operating temperature and preventing overheating, which prolongs the LED's lifespan and improves efficiency.
- **Industrial Durability:** The silicone coating on the PCB provides extra protection against dust, moisture, and other environmental factors, making the fixture resistant to the challenges of heavy industrial environments.
- **Efficiency and Speed:** The LED fixture provides sufficient power for fast and efficient performance, which is essential for industrial production systems that need to process or cure large amounts of material quickly.

## Technical specifications

General													
Brand	LuxaLight												
Application	Disinfection												
LED type	3535												
Material	Aluminum												
Dimensions	220 × 26,6 × 23,5 mm												
Mounting	Surface mounted												
LEDs per piece	60.00												
Lighting													
Wave length	365nm												
Beam angle	60 °												
Measurement results													
Irradiance	<table border="1"> <thead> <tr> <th>Value</th> <th>Measuring distance</th> </tr> </thead> <tbody> <tr> <td>1129 W/m<sup>2</sup></td> <td>100 mm</td> </tr> <tr> <td>414 W/m<sup>2</sup></td> <td>200 mm</td> </tr> <tr> <td>217 W/m<sup>2</sup></td> <td>300 mm</td> </tr> <tr> <td>120 W/m<sup>2</sup></td> <td>400 mm</td> </tr> <tr> <td>54 W/m<sup>2</sup></td> <td>600 mm</td> </tr> </tbody> </table>	Value	Measuring distance	1129 W/m <sup>2</sup>	100 mm	414 W/m <sup>2</sup>	200 mm	217 W/m <sup>2</sup>	300 mm	120 W/m <sup>2</sup>	400 mm	54 W/m <sup>2</sup>	600 mm
	Value	Measuring distance											
	1129 W/m <sup>2</sup>	100 mm											
	414 W/m <sup>2</sup>	200 mm											
	217 W/m <sup>2</sup>	300 mm											
	120 W/m <sup>2</sup>	400 mm											
54 W/m <sup>2</sup>	600 mm												
Electronics													
Working voltage	24V												
Current per piece	1.80 A / piece												
Power consumption per piece	43.20 W / piece												
PCB material	Aluminium												
Environmental													
Operating temperature	-20 ~ +60 °C												
Storage temperature	-40 ~ +80 °C												
IP class	IP 64												
Directives - standards - certificates													
Directives	RoHS CE												
Safety standards	EN60598-1 EN62031 IEC62471												

## Measurement results



While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.