

Datasheet

LuxaLight UV LED-strip 395nm Protected (24 Volt, 140 LEDs, 2835, IP64)

LS24UV395X140X2835PLX

Version: 2025-02-26.1

Product description

The **LuxaLight Industrial 395nm LED Strip** is designed for demanding industrial environments, providing an exceptionally effective UV-A lighting solution with a 395nm wavelength. This LED strip is perfect for applications such as curing, sterilization, reactor processes, and inspection. Featuring **140 high-performance LEDs**, the strip delivers uniform and consistent UV-A radiation with an impressive output of **309 W/m²** at a **distance of 2.5 cm**, ensuring powerful and reliable illumination for a wide range of industrial processes.

Designed with **IP64-rated protection**, the LED strip is resistant to dust, moisture, and other environmental contaminants, making it highly reliable in harsh conditions. Its robust and durable design is ideal for industrial applications such as UV curing, surface sterilization, reactor processes, and fluorescence detection.

Key Features:

- **395nm Wavelength:** Delivers effective UV-A radiation, perfect for curing, sterilization, reactor processes, and applications requiring precise UV light.
- **140 High-Performance LEDs:** Ensures uniform UV-A output with consistent radiation intensity, making it efficient and reliable for industrial applications.
- **Radiation Output of 309 W/m² at 2.5 cm Distance:** Provides a high radiation output of **309 W/m²** at **2.5 cm**, making it ideal for processes requiring focused and consistent UV-A energy.
- **IP64 Protection:** The LED strip is IP64-rated, offering protection against dust and water, making it suitable for use in industrial environments and other challenging settings.
- **Energy-Efficient:** Designed for high performance with low power consumption, the LED strip offers an energy-efficient lighting solution for UV-related applications.
- **Durable and Long-Lasting:** Built to last, the LED strip is reliable for continuous operation in demanding environments.

Applications:

- **UV Curing:** Ideal for curing adhesives, coatings, inks, and other materials in various industrial manufacturing processes.
- **Sterilization:** Perfect for surface sterilization in environments where disinfection is crucial, such as medical and laboratory settings.
- **Reactor Processes:** The 395nm UV-A output is perfect for driving photochemical reactions in UV reactors, such as those used in wastewater treatment, chemical synthesis, or polymerization processes. The precise and reliable UV-A energy ensures consistent results in these applications.
- **Fluorescence Detection:** Suitable for applications in research and quality control, where UV light is required for fluorescence-based imaging and detection.
- **Inspection Systems:** The LED strip is also ideal for machine vision systems, providing UV illumination to inspect materials, surfaces, or products in detail.
- **Printing and Coating Industry:** Enhances the efficiency of UV-based curing processes, particularly in industries such as printing and coating, where rapid curing is critical.

Benefits:

- **High and Consistent Output:** The **309 W/m² radiation output at 2.5 cm** ensures reliable and high-efficiency UV-A energy, optimizing the effectiveness of industrial processes.
- **Protection in Harsh Environments:** The **IP64 protection** guarantees durability against dust and water, ensuring reliable performance in industrial and other challenging environments.
- **Compact and Flexible:** The flexible design of the LED strip allows for easy installation in tight spaces and can be adapted to meet specific application requirements.
- **Long Service Life:** The robust construction of the LED strip ensures long-lasting performance, reducing the need for frequent replacements and offering greater cost efficiency.
- **Energy Efficiency:** High radiation output combined with low power consumption ensures an energy-efficient solution for UV applications in various industrial sectors.

Technical specifications

General

Brand	LuxaLight
LEDs / meter	140
LED type	2835
Length per reel	10 m
Length per segment	25 mm
LED strip width	12.00 mm
LED strip thickness	4.00 mm
PCB color	White
Mantle material	Silicon

Lighting

Wave length	395 nm
Beam angle	120 °

Measurement results

PPFD

Product length: 200 mm

Value	Measuring distance
319 µmol/m ²	25 mm
115 µmol/m ²	50 mm
53 µmol/m ²	75 mm
41,8 µmol/m ²	100 mm
13,1 µmol/m ²	200 mm
6,7 µmol/m ²	300 mm

Irradiance

Product length: 200 mm

Value	Measuring distance
309 W/m ²	25 mm
97,7 W/m ²	50 mm
47,5 W/m ²	75 mm
33,1 W/m ²	100 mm
10,1 W/m ²	200 mm
5 W/m ²	300 mm

Electronics

Working voltage	24V
Current / meter	1.00 A / meter
Power consumption per meter	24.00 W / meter
PCB material	Copper

Environmental

Operating temperature	-20 ~ +60 °C
Storage temperature	-40 ~ +80 °C

IP class IP 64


Directives - standards - certificates

Directives RoHS
CE

Safety standards EN60598-1
EN62031
IEC62471

Measurement results

Wavelength



While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.