Datasheet

LuxaLight Industrial LED Fixture Polarised cover Near Infrared 860nm 24.2x16mm (24 Volt, 2835, IP64)

LF-24-860-24.2X16-POL

Version: 2025-03-28.1

Email: info@luxalight.eu

Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04

Product description

The **LuxaLight Industrial LED Fixture** is designed for intensive industrial applications that require high radiation intensity for a wide range of processes. With **860nm near-infrared (NIR) radiation**, this LED fixture provides a reliable and efficient solution for industrial processes that benefit from **near-infrared radiation**, such as material curing, photochemical reactions, and quality inspection.

The fixture is made from a **durable aluminum housing**, ensuring efficient heat dissipation and long-lasting performance. The **polarized cover** offers protection against dust and moisture (IP64) and provides the flexibility to choose the radiation beam angle between **30°**, **60°**, **90°**, **or 120°**, depending on your specific application needs.

Key Features:

- 860nm Near-Infrared Radiation: The 860nm wavelength is ideal for industrial applications requiring near-infrared radiation, enhancing processes such as material curing, photochemical reactions, and quality inspection.
- Polarized Cover (IP64): The fixture features a polarized cover providing protection against dust and moisture (IP64), and offers a
 choice of radiation beam angle: 30°, 60°, 90°, or 120°, depending on the application.
- Aluminum Housing: The durable aluminum housing ensures optimal heat dissipation, contributing to stable and long-term operation.
- 24V Power Supply: The fixture operates on a reliable 24V power supply, ensuring stable and consistent performance, ideal for demanding industrial applications.
- Integration with MaNima Pollux Industry Pulsing (Strobing): The LED fixture supports integration with the MaNima Pollux Industry System for pulsing (strobing), significantly increasing radiation intensity. This feature enables faster reactions and enhanced efficiency in industrial processes.
- Real-Time Temperature Monitoring via NTC Sensor: The integrated NTC sensor allows continuous temperature measurement
 and adjustment via the MaNima Pollux Industry System. This helps maintain the optimal operating temperature for maximum
 radiation output and consistent performance.

Industrial Applications:

- Material Curing & Hardening: 860nm near-infrared radiation is commonly used in the curing process of coatings, adhesives, and materials that respond to infrared radiation, accelerating curing times in production environments.
- Photochemical Processes: The 860nm wavelength can be used in industrial and scientific environments where specific photochemical reactions are required, accelerating reactions in laboratories or production lines.
- Quality Control & Inspection: 860nm NIR is ideal for inspecting materials or products for defects or irregularities in industrial
 environments, improving quality control.
- Food Processing & Sterilization: The fixture is used in food production for sterilization and pasteurization, enhancing food safety and processing efficiency by delivering consistent near-infrared radiation.
- Non-UV Material Curing & Hardening: The 860nm radiation is used for curing various materials that do not require UV light but benefit from NIR wavelengths, such as plastics, rubbers, and other composite materials, speeding up the curing process.
- Natural & Artificial Drying: The 860nm wavelength helps dry a wide range of materials such as paper, textiles, and wood, by
 accelerating moisture evaporation without damaging the product. This is especially useful in printing and textile industries.
- Metal & Material Processing: 860nm NIR is applied to improve the properties of coatings or accelerate the curing of certain materials, reducing processing times in manufacturing and enhancing efficiency.

Benefits:

- **High Radiation Intensity for Faster Processes:** The fixture can pulse with the MaNima Pollux Industry System to increase radiation intensity, reducing processing time and increasing productivity in industrial applications.
- Real-Time Temperature Monitoring for Consistent Performance: Continuous temperature monitoring with the integrated NTC sensor helps maintain optimal operating temperatures, preventing overheating and ensuring a longer lifespan for the fixture.
- Industrial Durability: The aluminum housing provides a robust and durable construction, capable of withstanding the challenges
 of harsh industrial environments, while the polarized cover ensures protection against dust and moisture, increasing the fixture's
 reliability.

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04

 Efficiency & Speed: The LED fixture delivers efficient performance, with quick and reliable operation contributing to increased productivity and processing efficiency, essential for industrial production systems.

KvK-nummer: 57580561

BTW-nummer: NL852642209B01

IBAN: NL87 INGB 0007 8159 75

BIC/SWIFT code: INGBNL2A

Technical specifications

Compared					
General					
Brand	LuxaLight				
Application	Hyper - spectral Imaging Machine Vision				
LED type	2835				
Material	Aluminum				
Dimensions	220 × 24,2 × 16 mm				
Mounting	Surface mounted	Surface mounted			
Cover type	PMMA Polarised transparent				
LEDs per piece	108.00				
Lighting					
Wave length	860nm				
Measurement results					
Irradiance	Value	Measuring distance			
	283 W/m2	50 mm			
	139 W/m2	75 mm			
	88 W/m2	100 mm			
	26 W/m2	200 mm			
	13 W/m2	300 mm			
	7,9 W/m2 400 mm				
	5,2 W/m2	5,2 W/m2 600 mm			
	resulting in higher output.	onitoring, the efficiency of LED systems can be increased, orm measurements tailored to the specific requirements of			
Electronics					
Working voltage	24V				
Current per piece	1.25 A / piece				
Power consumption per piece	30.00 W / piece				
PCB material	Aluminium				
Pinout	Symbol	Function			
	V+	V+			
	GND	Ground			
	NTC	NTC sensor			
	NTC_GND	NTC ground			
NTC parameters	Resistance: 5000 Ohm Beta value: 3950				
Environmental					

Operating temperature

-20 ~ +60 °C

Storage temperature	-40 ~ +80 °C
IP class	IP 64
Directives - standards - certificates	
Directives	RoHS CE

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04