Datasheet

LuxaLight COB LED-strip White 5500K Waterproof (12 Volt, 512 LEDs, COB, IP68)

LS12WCOBWLX5500K

Version: 2025-03-10.3

Product description

The LuxaLight Professional COB LED Strip is a high-quality lighting solution, ideal for use in various indoor and outdoor environments. This strip is designed with a vulcanized silicone sleeve and has an IP68 certification, meaning it is fully dust- and waterproof, making it suitable for a wide range of applications, even in the most demanding environments. The strip utilizes advanced COB LED technology and offers a color temperature of 5500K with excellent color rendering (CRI > 95). These features make the LED strip perfect for applications where natural lighting is required, such as in living spaces, work areas, retail environments, and more.

Key Features:

- Color Temperature of 5500K: The 5500K lighting provides bright, cool white light that is ideal for workspaces, commercial environments, and other applications that require bright lighting.
- CRI (≥95): The excellent color rendering ensures natural lighting, with colors appearing vivid and true-to-life, which is essential for applications in retail, museums, and healthcare facilities.
- Vulcanized Silicone Sleeve and IP68 Certification: The strip is encased in a robust vulcanized silicone sleeve and is IP68 certified, providing full protection against dust and water. This makes it suitable for use in environments where the strip may be exposed to water, such as outdoor spaces, gardens, pools, and other wet environments.
- **COB LED Technology:** Instead of traditional individual LEDs, this strip uses COB (Chip-on-Board) LED technology, ensuring uniform light distribution without visible hotspots. This results in a more consistent and efficient lighting solution.
- Use of 3M 4905 VHB Tape: The strip is equipped with 3M 4905 VHB tape, ensuring a strong and reliable attachment to various surfaces.

Applications:

- Residential and Work Spaces (indoor): The cooler 5500K color temperature and high CRI value make this professional LED strip ideal for creating bright and functional lighting in workspaces, kitchens, offices, and meeting rooms.
- Retail and Window Displays: The excellent color rendering ensures that products in stores and window displays are presented in the best possible light. The IP68 certification makes the strip suitable for use in commercial environments, both indoors and outdoors.
- Museums and Galleries: The cooler lighting and high color rendering are perfect for illuminating artworks and objects in museums, galleries, and exhibitions, where color integrity is crucial.
- Healthcare and Medical Facilities: The cooler, natural lighting is ideal for healthcare facilities, where proper lighting is important for the well-being of patients and staff.
- Outdoor Spaces and Pools: The IP68 certification makes this LED strip fully waterproof and suitable for use in outdoor environments such as gardens, patios, and pools, where the strip may be exposed to water and weather conditions.

Advantages:

- Excellent Color Rendering: With a CRI of over 95, this professional LED strip provides accurate and natural color rendering, ideal for applications where color perception is essential.
- Cool Lighting: The 5500K color temperature provides bright, cool white light, perfect for workspaces and commercial spaces that require bright lighting without feeling too warm.
- Flexible and Customizable: Thanks to its flexible design, the strip can easily be integrated into various lighting setups and fixtures, making it a versatile solution for a wide range of applications.
- Uniform Light Distribution: COB LED technology ensures consistent and even light distribution, providing pleasant and comfortable lighting without harsh shadows or hotspots.
- Reliable Performance: The LED strip operates on a standard 12V power supply and offers efficient, stable performance, making it ideal for long-term use in both residential and commercial environments.
- **Durable and Energy-Efficient:** LED technology is energy-efficient, meaning the strip is not only cost-effective but also contributes to a more sustainable lighting solution.
- Strong Adhesion: The 3M 4905 VHB tape provides reliable adhesion for easy and durable installation on various surfaces.


Technical specifications

General	
Brand	LuxaLight
LEDs / meter	512
LED type	СОВ
Length per reel	10 m
Length per segment	25 mm
LED strip width	12.00 mm
LED strip thickness	5.00 mm
PCB color	White
Mantle material	Silicon
Warranty	5 years
Lifetime	70000 hours
Lighting	
Color temperature	5500 K
CRI	≥ 95
Luminous Flux	1490 lm
BIN	3 SDCM
Beam angle	120 °
LB waarde	L90B20
Electronics	
Working voltage	12V
Current / meter	1.25 A / meter
Power consumption per meter	15.00 W / meter
PCB material	Copper
Environmental	
Operating temperature	-20 ~ +60 °C
Storage temperature	-40 ~ +80 °C
IP class	IP 68
Directives - standards - certificates	
Directives	RoHS CE
Safety standards	EN60598-1 EN62031 IEC62471

2 Zirqle LuxaLight®


Measurement results

WAVELENGTH



KvK-nummer: 57580561 BTW-nummer: NL852642209B01 IBAN: NL87 INGB 0007 8159 75 BIC/SWIFT code: INGBNL2A Email: info@luxalight.eu Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04

CIE1931



KvK-nummer: 57580561 BTW-nummer: NL852642209B01 IBAN: NL87 INGB 0007 8159 75 BIC/SWIFT code: INGBNL2A Email: info@luxalight.eu Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04 While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.

KvK-nummer: 57580561 BTW-nummer: NL852642209B01 IBAN: NL87 INGB 0007 8159 75 BIC/SWIFT code: INGBNL2A Email: info@luxalight.eu Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04