

# Datasheet

**LuxaLight LED-strip Warm White 2600K Protected (24 Volt, 140 LEDs, 2835, IP64)**

**LS24WW140X2835PLX**

**Version: 2025-03-03.2**

## Product description

The **LuxaLight Professional LED Strip** is a high-quality lighting solution, ideal for use in various indoor environments. This strip is designed with a **silicone layer** and features an **IP64** certification, making it dust and splash-resistant, which makes it suitable for a wide range of applications. The strip features **140 2835 LEDs** per meter and offers a warm 2600K color temperature with excellent color rendering (CRI > 95). These features make the LED strip perfect for applications that require true-to-life lighting, such as in living spaces, workspaces, retail environments, and more.

### Key Features:

- **2600K Color Temperature:** The warm 2600K lighting creates a cozy and inviting atmosphere, ideal for use in living rooms, offices, and commercial environments.
- **High CRI (≥95):** The excellent color rendering ensures true-to-life lighting, with colors being displayed brightly and vividly, essential for applications in retail, museums, and healthcare settings.
- **Silicone Layer and IP64 Certification:** The strip features a durable silicone layer and is **IP64** certified, providing protection against dust and water splashes. This makes the strip suitable for use in environments with limited exposure to moisture, such as wet rooms (e.g., bathrooms).
- **140 2835 LEDs per meter:** This LED strip features **140 2835 LEDs** per meter, ensuring even and efficient light distribution.
- **3 oz/ft<sup>2</sup> PCB Thickness:** The PCB has a thickness of 3 oz/ft<sup>2</sup>, which provides robust support and efficient heat dissipation, making the strip reliable and durable.
- **3M 4905 VHB Tape:** The strip is equipped with **3M 4905 VHB tape**, ensuring a strong and reliable attachment to various surfaces.

### Applications:

- **Residential and Office Spaces (indoor):** The warm 2600K color temperature and high CRI value make this professional LED strip ideal for creating pleasant, true-to-life lighting in living rooms, offices, and conference rooms.
- **Retail and Display Windows:** The excellent color rendering ensures that products in stores and display windows are showcased at their best. The **IP64** certification makes the strip suitable for use in commercial environments exposed to light water splashes.
- **Museums and Galleries:** The warm lighting and high color rendering are perfect for illuminating artworks and objects in museums, galleries, and exhibitions, where color integrity is of utmost importance.
- **Healthcare and Medical Settings:** The warm, true-to-life lighting is ideal for healthcare settings, where lighting plays a key role in the well-being of patients and staff.
- **Wet Rooms:** The **IP64** certification makes this LED strip suitable for use in wet rooms, such as bathrooms, where occasional contact with water splashes is possible.

### Benefits:


- **Excellent Color Rendering:** With a CRI of over 95, the professional LED strip provides accurate and natural color rendering, making it ideal for applications where color perception is crucial.
- **Warm Lighting:** The 2600K color temperature delivers a soft, warm glow, ideal for creating a comfortable and inviting atmosphere in various environments.
- **Flexible and Customizable:** Thanks to the flexible design, the strip can be easily integrated into various lighting setups and fixtures, making it a versatile solution for diverse applications.
- **Uniform Light Distribution:** With 140 pcs 2835 LEDs per meter, the strip offers consistent and uniform light distribution, ensuring pleasant and comfortable lighting without harsh shadows.
- **Reliable Performance:** The LED strip operates on a standard 24V power supply and provides efficient, stable performance, making it an ideal choice for long-term use in both residential and commercial environments.
- **Durable and Energy-Efficient:** LED technology is energy-efficient, meaning the strip is not only cost-effective but also contributes to a more sustainable lighting solution.
- **Strong Adhesion:** The 3M 4905 VHB tape provides reliable adhesion for easy and durable installation on various surfaces.

## Technical specifications


General	
Brand	LuxaLight
LEDs / meter	140
LED type	2835
Length per reel	10 m
Length per segment	50 mm
LED strip width	10.00 mm
LED strip thickness	4.00 mm
PCB color	White
Mantle material	Silicon
Warranty	5 years
Lifetime	70000 hours
Lighting	
Color temperature	2500 ~ 2700 K
CRI	≥ 95
Luminous Flux	≈ 3000 lm
BIN	3 SDCM
Beam angle	120 °
LB waarde	L90B50
Electronics	
Working voltage	24V
Current / meter	1.00 A / meter
Power consumption per meter	24.00 W / meter
PCB material	Copper
Environmental	
Operating temperature	-20 ~ +60 °C
Storage temperature	-40 ~ +80 °C
IP class	IP 64
Directives - standards - certificates	
Directives	RoHS CE
Safety standards	EN60598-1 EN62031 IEC62471

## Measurement results

### WaveLength



CIE1931



While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.